

Instruction # 8102
SKU: 120-90347



Leveling kit for 2005 to 2016 Ford Super Duty F250 and F350 4WD

CAUTION: Installation must be performed by a qualified mechanic. Installation by an un-qualified mechanic may result in an unsafe vehicle/ and or personal injury.

*****Upon completion of the installation, headlight adjustment and front end alignment are required*****

Note: It is necessary to raise the vehicle to perform installation of these products. A hoist or installation bay is recommended. Always ensure the truck is properly supported before attempting installation as serious injury could occur.

Parts List

- (2) coil spring spacer
- (2) 14mm-2.0x100mm hex bolt
- (2) 14mm lock washer
- thread locker

Instruction # 8102
SKU: 120-90347

INSTRUCTIONS:

1. raise vehicle with car hoist or jack and jack stands, never work on an unsupported vehicle.
2. remove the front wheels.
3. use a jack to support underneath the front axle housing, Figure 1



Figure 1

4. Remove the lower shock bolts, brake line bracket from the housing, and the lower sway bar end links.
5. now lower the axle housing so that the coil springs are removable from the truck as shown in Figure 2. Remove the springs from the truck along with the upper coil spring isolator, retain for re-installation.
6. unbolt the factory lower coil spring perch from the axle housing shown in figure 3, discard the hardware but retain the perch.

Instruction # 8102
SKU: 120-90347



Figure 2



Figure 3

7. As shown in Figure 4, re-install the factory spring perch with the supplied coil spacer to space the perch above the housing from the stock location. Fasten the spacer and perch with the supplied bolt and lock washer, and place a small amount of thread locker on the bolt, then torque to 100 ft. lbs. repeat on other side of vehicle.
8. now install the coil spring and isolator back into place, raise the floor jack until the spring is in the proper position, and compressed slightly so that the shock, brake line bracket, and sway bar end link can be re fastened. The metal brake line must be bent slightly toward the front of the truck as shown in Figure 5.

Instruction # 8102
SKU: 120-90347



Figure 4



Figure 5

9. re-install wheel and torque lug nuts to factory specs
10. re-adjust the headlights per owner's manual, and have the front end professionally aligned to factory specifications.
11. the vehicle will handle differently due to increased ride height, please take time to familiarize yourself with the handling characteristics of your modified vehicle.

Instruction # 8102
SKU: 120-90347

Cognito Limited Lifetime Warranty

Cognito Motorsports, Inc. hereinafter "Cognito," warrants to the original retail purchaser, that its suspension products are free from workmanship and material defects for as long as the purchaser owns the vehicle on which the product(s) were originally installed. This warranty will be void if any modifications are made to the components, including alterations to the surface finish, i.e.; painting, powder coating, plating, and/or welding, or if they are improperly installed. Cognito truck suspension products are not designed nor intended to be installed on "competition" vehicles used in race applications, stunt or for exhibition purposes that are outside of the intended operating conditions specified by the manufacturer. Racing and competition are defined as any contests between two or more vehicles; or vehicles competing individually on off road circuits in timed events (whether or not such contests are for an award or prize).

This warranty does not include coverage for police, taxi, government or commercial vehicles, and the warranty does not cover Cognito products sold outside of the USA. Cognito's obligations under this warranty are specified and applied at its sole discretion, and warranty coverage is limited to repair or replacement of the defective product(s). Any and all costs of removal, installation or reinstallation; freight charges, incidental or consequential damages associated with the covered products are expressly excluded from this warranty.

The following items are exempt from Cognito limited warranty coverage: bushings, bump stops, tie-rod ends (Heim joints) and limiting straps. These parts are "consumables" and designed to wear as a normal part of their duty cycle, therefore they are not considered defective when worn. The aforementioned products are warranted separately against defects in workmanship, for 60 days from the date of purchase. As a condition of warranty validation, respective Cognito suspension components must be installed as a complete system (not combined with non-Cognito hardware or ancillary parts). Any substitutions or omission of required components will void the warranty. Some minor cosmetic wear and imperfections may occur to parts during shipping, which is not covered under this warranty. This limited warranty does not apply to any components that have been subjected to collision damage, negligence, alteration, abuse, or misuse, and coverage does not extend to products manufactured by third-party companies. Cognito reserves the right to supersede, discontinue, or change the design, finish, part number and/or application of its parts when deemed necessary, without notice.

Return Policy

Product returns will not be accepted without prior written approval from an authorized Cognito representative. All products being returned must be shipped via trackable, prepaid freight. Returned products are subject to a 25% percent restocking fee. The eligible return period for products purchased directly from Cognito is 30 days from the verified date when the product(s) were originally received by the purchaser.

Product Safety Advisory

The installation of Cognito steering and suspension components will modify your vehicle's original factory equipment and geometry, which may cause it to handle differently than a stock (unaltered) vehicle. Installation of these components is not intended to strengthen nor reinforce the vehicle's frame, nor are they designed to increase rollover protection. It is necessary to periodically inspect all suspension and drive train components for proper attachment, torque specifications, operation, and for any potential unusual wear or damage. Installation of these parts will modify the height of the vehicle and may raise the center of gravity. Modifying vehicle height combined with off road operation may increase your vehicle's susceptibility to rollover conditions, which may cause serious injury or death. Many states regulate allowable vehicle height modifications, and it is your responsibility to know and comply with the legal requirements specified by the laws where you reside. Modifications to your vehicle's ride height may also affect the ride quality, driver input response, trackability and handling, and wear to your vehicle's suspension components and tires.